



CAN COATING RESINS

SP-EAGLE (TS-140N60) 60%: Saturated polyester resin for general purpose SP-EAGLE (TS-50N60) 60%: Saturated polyester resin for white base coat

AC-EAGLE (TS-22M55) 58%: Thermosetting hydroxyl acrylic resin

COIL COATING RESINS

SP-EAGLE (TS-40NBG65) 65%: Saturated polyester resin for topcoat superdurable

SP-EAGLE (TS-30NBG65) 65%: Saturated polyester resin for topcoat with high reactivity and for

back coating

PROPERTIES

	N.V%	Visc	A.V	OH value	Color	
Can coating resins						
SP-EAGLE(TS-140N60) 60%	60	Z4-Z5	5-10	25	2 MAX (G)	
SP-EAGLE(TS-50N60) 60%	60	Z3-Z4	4-7	45	3 MAX (G)	
AC-EAGLE(TS-22M55) 58%	58	Z1-Z3	6-17		50 MAX (H)	
Coil coating resins						
SP-EAGLE(TS-40NBG65)65%	65	Z2-Z3	0-4	35-45	3 MAX (G)	
SP-EAGLE(TS-30NBG65)65%	65	Z1-Z2	2-7	110	3 MAX (G)	

APPLICATIONS

SP-EAGLE(TS-140N60)60%: Tube coatings, white base coats

SP-EAGLE(TS-50N60)60%: White base coat for general line

AC-EAGLE (TS-22M55) 58%: Can coating, two piece can base coating, external lines and twist

off lids, crown and screw caps

SP-EAGLE(TS-40NBG65)65%: Top coat superdurable coil coatings SP-EAGLE(TS-30NBG65)65%: Top coat for interior and exterior use

CHARACTERISTICS

SP-EAGLE(TS-140N60)60%: Flexibility, deep drawing and cold crush

SP-EAGLE(TS-50N60)60%: Flexibility, sterilization resistance

AC-EAGLE (TS-22M55) 58%: Good sterelization resistance, flow, acceptance to UV curable

printing ink and deep drawing

SP-EAGLE(TS-40NBG65)65%: Super durablity - excellent QUV resistance

SP-EAGLE(TS-30NBG65)65%: Outdoor durablity -very good weathering resistance



EL Shark Company for trade & industry / Eagle Polymers Company

www.eagle-chemicals.com

Tel :: 0020 -2 -38329871/2 Fax:: 0020 -2 -38311481

Export Marketing

Local Marketing

 $\textbf{E-mail:} \ local-marketing@eagle-chemicals.com$